

# SAFETY DATA SHEET

**Trade Name:** AQUASET HARDENER

**Chemical Family:** Cycloaliphatic Amine

**Formula:** Proprietary

**Distributed by:** ST. LAWRENCE CHEMICAL INC. **Supplier:** COAST FIBER-TEK  
19201 Clark Graham Ave. 1306 Boundary Road  
D'Urfé, Qc. H9X 3P5 Burnaby, BC V5K 4T6

**Emergency Phone #'s:** (800) 526-9374

**Transportation EMG. Phone #** CANUTEC (613) 996-6666  
(604) 930-0650

## HAZARDOUS INGREDIENTS:

1. Isophoronediamine	<35%	CAS # 2855-13-2
2. Phenol:	<10%	CAS # 108-95-2
3. Benzyl Alcohol:	>35%	CAS # 100-51-6

Exposure Limits: 2. LD50 oral rat 317 mg/kg, LD50 dermal rat 669mg/kg, LD50 dermal rabbit 630 mg/kg  
3. LD50 oral rat 1230 mg/kg, dermal rabbit 2000 mg/kg, LC50 inhalation rat 500 mg/m3

## PHYSICAL DATA:

Appearance & Odour: Light yellow liquid, irritating odour

Vapour Pressure: < 10.34 mmHg @ 21 °C

Vapour Density: N/A

Solubility in Water: <0.1 g/l

Specific Gravity: 1.02 @ 20 °C

Boiling Point: 204 °C

PH (As Is): Alkaline

Boiling Point: 204 °C

## FIRE & EXPLOSION DATA:

Flashpoint & Method: >110°C, (PMCC )

Flammable Limits: N/A

Extinguishing Methods: CO<sub>2</sub>, dry chemical, foam, dry sand, Limestone powder

Special Equipment & Procedures: Self-contained breathing apparatus & complete protective clothing should be worn fighting chemical fires.

## REACTIVITY DATA:

Conditions Contributing to Instability: Moisture, contact with incompatible products.

Incompatible Substances: Sodium hypochlorite, organic acids, mineral acids, reactive metals, materials reactive with hydroxyl compounds, oxidizing agents.

Product slowly corrodes copper, aluminum, zinc, and galvanized surfaces. Reaction with peroxides may result in violent decomposition of peroxide possibly creating and explosion.

Hazardous Decomposition Products: (under fire conditions) Nitric acid, ammonia, oxides of nitrogen, carbon monoxide, carbon dioxide, aldehydes, hydrocarbons

Hazardous Polymerization: Will not occur by itself.

## HEALTH HAZARDS DATA:

**NOTE:** Health studies have shown that exposure to chemicals pose potential risks which may vary from person to person. Exposure to liquids, vapours, mists or fumes should be minimized.

# MATERIAL SAFETY DATA SHEET

Aquaset Hardener - Pg 2

## **PRINCIPAL HEALTH HAZARDS:**

- Skin Contact:** If absorbed through the skin, may cause headache, nausea, dizziness, confusion, breathing difficulties.
- Eye Contact:** Causes severe eye irritation. Product vapour can cause lacrimation, conjunctivitis and corneal edema when absorbed into the tissue of the eye from the atmosphere.
- Ingestion:** Harmful if swallowed. May cause headache, nausea, vomiting, abdominal pain, dizziness, confusion and breathing difficulties.
- Inhalation:** May cause delayed lung injury. May cause headache, nausea, dizziness, confusion, breathing difficulties, coughing, lung irritation, upper respiratory irritation.

## **FIRST AID PROCEDURES:**

- Skin:** Wash off in flowing water.
- Eyes:** Flush with warm water for 20 minutes, obtain medical attention.
- Ingestion:** **DO NOT INDUCE VOMITING.** Seek medical attention.
- Inhalation:** Remove to fresh air if ill effects develop. If effects persist administer oxygen, apply A/R if necessary and seek medical attention.

## **PREVENTIVE MEASURES:**

- Skin:** Always apply appropriate barrier cream to exposed skin. Wear impervious gloves (butyl rubber), coveralls and safety footwear.
- Eyes:** Chemical proof goggles or full face respirator if vapours cause eye irritation.
- Ingestion:** Wash thoroughly before consuming food stuffs.
- Inhalation:** Use only in well ventilated areas or use NIOSH or CAS approved respiratory protection with organic vapour cartridges.

## **CONTROL MEASURES & PRECAUTIONS**

Keep container tightly closed. Do not consume food, drink or tobacco in work area or material storage areas. Use caution and personal cleanliness to avoid skin and eye contact. Avoid breathing vapours of heated materials. Use paper covering absorbent wipes and suitable disposable containers in work area.

## **SPILL, LEAK & DISPOSAL METHODS**

**Review fire and explosion hazards and safety precautions before proceeding with clean up.** Restrict access to area. Contain spill to prevent liquid from entering sewers or waterways. Recover free liquid and use an absorbent material (i.e. sand, vermiculite) to soak up balance. Place in suitable container for disposal.

## **DISPOSAL METHOD**

Dispose only in a facility permitted to dispose of hazardous waste by Federal, Provincial and Municipal regulations.

## **SHIPPING INFORMATION**

- Shipping Name:** Amines, Corrosive Liquid N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine)
- Hazard Class:** 8
- UN/PIN #:** 2735 III
- Flashpoint:** 110°C
- WHMIS:** DIA, D2B, E

The information contained herein is based on data that we believe to be accurate. No warranty either expressed or implied is made. This information is offered solely for your consideration interpretation and information.

- Preparation Date:** January 31, 1993
- Prepared by:** Nigel Poore, 1306 Boundary Road, Burnaby, BC V5K 4T6
- Telephone #:** (604) 294-8116
- Revised Date:** July 5, 2016

N/A = Not Available